ZONE 2/22

IS730.2

The IS730.2 is the resistant ATEX-smartphone for use in zone 2/22. It combines high performance technology with highest robustness and modern design.

WWW.ISAFE-MOBILE.COM

EN

‹ **i.safe MOBILE** ›

TECHNICAL FEATURES

ATEX approval: EX-zone 2/22 Ⓔ II 3G Ex ic IIC T4 Gc IP54 Ⓔ II 3D Ex ic IIIB T135°C Dc IP54	IECEx approval: EX-zone 2/22 Ex ic IIC T4 Gc IP54 Ex ic IIIB T135°C Dc IP54	Android 6.0

2G: GSM 850/900/1800/1900 MHz
3G: WCDMA 850/900/1900/2100 MHz
4G: LTE-FDD Band 1/3/7/20/28,
LTE-TDD Band 39/40/41

WiFi IEEE 802.11 b/g/n

Bluetooth® 4.0

MT6735 (Quad Core 1.3 GHz), 2 GB RAM, 16 GB internal memory, 10 GB assessable

size: 156 x 82 x 14 mm, weight: 245 g

external memory microSD up to 32 GB

Dual micro SIM

2 cameras:
13 MP rear camera and 5 MP front camera

Near Field Communication (only Android 6.0)

USB OTG

FURTHER FEATURES

IP68 waterproof: 30 min. up to 2 m, impervious to dust and microparticles

operation range from -20 °C to 60 °C

MIL-STD 810G drop-protection, tested against: extreme temperatures, barometric pressure, humidity and vibrations.

5" (12.70 cm) HD Bright View Gorilla Glass 3, capacitive touchscreen with a resolution of 1280 x 720 pixel

amplified loudspeaker

3.020 mAh battery, standby 450 hrs., talktime 2G/3G:
480 min./420 min.

GPS, AGPS, GLONASS, BeiDou (localization and navigation via application of another provider)

G-sensor, gyroscope light sensor, magnetic sensor, pressure sensor, proximity sensor

PTT Push-To-Talk PTT ready (third party application provided)

CONTENTS

Mobile phone with integrated battery, charger, USB cable, quick start manual and safety instructions